

NO HOLES MOUNT (NHM)

2002-2008 DODGE RAM - COMPUTER MOUNT

Specification Sheet

425-5349/5215

DETAILED INFORMATION

No Holes Mount	
Height Variation	19" to 24"
Swing Arm	1" square x 13 3/8" · Solid Aluminum, Black Anodized
Telescoping Rod	7/8" x 12" \cdot Steel \cdot 5/8" turned swing arm rest
Stand	1" x 10" ·11 Gauge Steel, Black · Round Stock
Base	3/16" Gauge Master ·One-piece Base ·Tapped 7/8" Mounting Post

ACD (ABS Cable-Dock® Desktop)

Length	12 "
Width	10"
Height	1"
	·ABS Plastic · 1/4" Wall Thickness · 22" Cables

· 6" Square 11 Gauge Steel Mounting Plate 5/8" Aluminum Post Connector



WHY THE CABLE-DOCK™ DESKTOP?

The Cable-Dock™ is a patented, truly innovative and proven method for effectively securing a laptop computer in a mobile environment.


- We provide shock absorbing pads while others don't.
- We allow air to circulate underneath the laptops while others don't.
- We embrace and conform to the whole body of the laptop rather than just contain the edges and sides as others do. Why? All laptops are not equal
- We have built-in back-up for keeping the laptop secure in case cable latch release is accidentally opened while others don't.
- We mount all sizes of laptops while others can't.
- We are lightweight at 3.4 lbs with two adjustments for set-u while others weigh 9-10 lbs, with 7-10 adjustments.

HOW TO ORDER

Computer Mount Package 425-5349/5215 (ACD)

Includes: Desktop, Swing Arm, Telescoping Rod,

Base 425-3075





ABS Cable Dock® Desktop

Rotates 360° with ergonomic platform tilt. Two (2) nylon coated stainless steel cables secure notebook computer to desk. "One Hand" operation for removing and securing computer. Six (6) foam pads lift the computer off of the desktop providing shock absorption and air flow under computer.

Rotates 360° around stand and extends 6 3/4". Ratchet Handles secure swing arm in position at elbow and stand.

Telescoping Rod

Extends desktop height. Travels inside of stand.

Ratchet Handles

Secures swing arm positioning and allows for 360° swing arm rotation.

Stand attaches to base and houses Telescoping Rod.

Telescoping Tripod Support

Two Brace kits attached to the stand provide additional support. Both braces can be mounted to varying flat, vertical or angled surfaces.

One Piece Mounting Base

3/16" gauge steel, one-piece base design increases overall sturdiness and frees up leg room.



